

# TraceTek Liquid Hydrocarbon & Water Leak Detection Systems

**Raychem**

Fm Class Number 7745 Approved



**RAYCHEM TRACETEK LIQUID HYDROCARBONS AND WATER LEAK DETECTION SYSTEMS ARE APPROVED PER FM STANDARD 7745**

## Our systems and products:

- Meet all requirements of FM class number 7745, most importantly the production of an alarm signal within 30 seconds of leak detection
- Have been on the market and continuously improved since the 1980's and have become the gold standard for comprehensive and preventative leak detection solutions
- Are trusted, reliable, durable and a critical part of safeguarding property and people while minimizing environmental damage
- Improves safety and aids in the prevention of property damage and business disruption
- Designed and manufactured with high performance polymers for long-term service



# TraceTek Liquid Hydrocarbon Leak Detection

## TRACETEK LIQUID HYDROCARBONS LEAK DETECTION SYSTEM OFFERS:

- Sensor cables and probes that directly detect and pinpoint the source of diesel leaks to help you take decisive action before the spill can create damage.
- Configuration options that automatically shut off pumps or valves where appropriate.
- Digital communications such as local, networked remote alarms and diagnostics including building management systems, email, or SMS.
- Modular and scalable units so that simple or complex systems can be configured for current needs and allow for future expansion.

## TYPICAL INDOOR LIQUID HYDROCARBONS FUEL MONITORING APPLICATIONS:

- Beneath day tanks
- Around pump pads
- Below valves or other flanged fittings
- Near threaded indoor pipe couplings
- At flexible hose couplings to engine injector pumps

## TraceTek Leak Detection System Components:

### TTDM-128 ALARM MODULE



- Multiple event tracking capability for up to 127 independent sensor circuits
- Complete remote operation and monitoring through Modbus communications
- Directly monitors up to 1500 m (5000 ft) of sensor cable and/or three TT-FFS probes

### TTSIM-1A OR TTSIM-2 SENSOR INTERFACE MODULE



- Monitors up to 150 m (500 ft) of TraceTek sensing cable and up to three TT-FF probes per circuit
- Can communicate to a monitoring system such as a TraceTek TTDM-128 or directly to a PLC or other host system using standard protocols
- Can be standalone leak detection alarm unit, or in networks with other TraceTek modules
- Available in 12 Vdc, 24 Vdc, 24 Vac, 120 Vac, and 230 Vac versions

### TT-FFS FAST FUEL SENSOR



- Fast response (within seconds) to small amount of fuel
- Resets for multiple uses
- Wet or dry locations (ignores water)

### TT5000 FUEL SENSING CABLE\*



- Detects the presence of liquid hydrocarbon fuels at any point along its length
- Does not react to the presence of water
- Designed for a variety of applications, including tanks, trenches and piping
- Locates the source of any detected leak to +/- 1 m (3 ft)

\*TT5000 does not meet FM 7745 requirement of producing a 30 second alarm, but can still be included in a diesel leak detection system

# TraceTek Water Leak Detection

## TRACETEK WATER LEAK DETECTION SYSTEM OFFERS:

---

- Cables and probes that directly detect and accurately pinpoint the source of the leak without the risk of digital communications and power running through the sensor cable out on the data center floor.
- Digital communications such as local, networked remote alarms and diagnostics including building management systems, email, or SMS that gives the ability to track many leaks at once.
- Configuration options that automatically shut off pumps or valves where appropriate.
- Modular assembly means systems can be configured for current needs and allow for future expansion.

## TYPICAL INDOOR WATER MONITORING APPLICATIONS:

---

- Raised floor computer facility
- ISP/co-location facilities
- Fiber optic switch sites
- Control rooms
- Trading rooms
- Archival storage
- Executive offices
- Communications and server equipment rooms
- Museums and historic buildings
- Libraries and aquariums
- Raised floor office areas
- Utility riser columns
- Elevator pits

## TraceTek Water Leak Detection System Components:

### TT-TS12

---



- Graphical User Interface
- Provides Leak Alarm, Status location information and dynamic leak mapping
- Manages and displays data from network of up to 250 SIMS

### TTSIM-1A

---



- Monitors up to 150 m (500 ft) of TraceTek sensing cable and up to three TT-FF probes per circuit
- Can communicate to a monitoring system such as a TraceTek TTDM-128 or directly to a PLC or other host system using standard protocols
- Can be standalone leak detection alarm unit, or in networks with other TraceTek modules
- Available in 12 Vdc, 24 Vdc, 24 Vac, 120 Vac, and 230 Vac versions

### TT1000

---



- TT1000 cable core is built with tough engineering plastics suitable to take the load and stress from being on the bottom layer of an under floor cable stack
- Made with conductive polymer technology, this rugged cable construction is resistant to corrosion and abrasion, and has no exposed metal parts
- Quick drying
- Detects the presence of water anywhere along its length
- UL Listed and Rated Type CL2P for plenum use
- Complies with NFPA 262 - "Standard Method of Test for Flame Travel and Smoke of Wires and Cables for use in Air-Handling Spaces"

**North America**

Tel +1 800 545 6258  
info@chemelex.com

**Latin America**

Tel +1 713 868 4800  
info@chemelex.com

**Europe, Middle East, Africa, India**

Tel +32 16 213 511  
Fax +32 16 213 604  
info@chemelex.com

**Asia Pacific**

Tel +86 21 2412 1688  
infoAPAC@chemelex.com



**Raychem Tracer Pyrotenax Nuheat**