

Elexant 4020i Control Module



nVent RAYCHEM ELEXANT 4020i-MOD is a set of replacement modules for the Elexant 4020i heat tracing controller.

FEATURES

Available with intrinsically safe barrier and limiter.

Simple to install

Reliable during long life: 2 year product warranty available

SPECIFICATIONS

Current Alarm: 0.1 – 100 A

Autocycle: 1 - 750 h

Ground Fault Alarm: 10 – 500 mA

Ethernet: 10/100 Base-T

Max Power Supply Input Wire Size: 16.8 mm²

Max Heating Cable Output Wire Size: 16.8 mm²

Max Ground Terminal Wire Size: 16.8 mm²

Control Max Current: 63A @ 40°C

Voltage Alarm: 80 – 300 V

Control Max Voltage: 690 VAC Nominal, 50/60Hz

Relative Humidity: 0% to 90%, Noncondensating

Control Relay Type: Double-Pole, Solid-State; Double-Pole, Mechanical

Communication: RS-485; Ethernet

Communication Protocol: Modbus RTU; Modbus/TCP

Control Algorithms: On/Off, Proportional, PASC, Always On, Always Off

Temperature Control Range: -200 to 700 °C

Temperature Alarm: -200 to 700 °C

Operating Temperature: -40 to 70 °C

Table 1/1				
Catalog Number	Item Name	RS-485 Cable Type	Safety Limiter	Intrinsically Safe Barriers on RTD Inputs
10380-020	4020i-MOD	One 2-Wire, Shielded Twisted Pair	No	No
10380-021	4020i-MOD-IS	One 2-Wire, Shielded Twisted Pair	No	Yes
10380-022	4020I-MOD-IS-LIM	2-Wire One Shielded Twisted Pair	One Dedicated Temperature Input	Yes
10380-024	4020i-MOD-3P-IS	2-Wire One Shielded Twisted Pair	No	Yes

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America

Tel +1.800.545.6258 Fax +1.800.527.5703 thermal.info@nvent.com Europe, Middle East, Africa

Tel +32.16.213.511 Fax +32.16.213.604 thermal.info@nvent.com **Asia Pacific**

Tel +86.21.2412.1688
Fax +86.21.5426.3167
cn.thermal.info@nvent.co
m

Latin America

Tel +1.713.868.4800 Fax +1.713.868.2333 thermal.info@nvent.com