

水平横梁，前端，R-KD 型，加固型，短舌，84 HP

物料号

34566-284



Combinations of horizontal rails and side panels

“+” = can be combined, “-” = combination not recommended

	Standard 1.0	Standard 1.5	Standard 2.0	Standard 2.5
Standard 1.0	-	+	+	+
Standard 1.5	+	+	+	+
Standard 2.0	+	+	+	+
Standard 2.5	+	+	+	+
Standard 3.0	+	+	+	+
Standard 3.5	+	+	+	+
Standard 4.0	+	+	+	+
Standard 4.5	+	+	+	+
Standard 5.0	+	+	+	+
Standard 5.5	+	+	+	+
Standard 6.0	+	+	+	+
Standard 6.5	+	+	+	+
Standard 7.0	+	+	+	+
Standard 7.5	+	+	+	+
Standard 8.0	+	+	+	+
Standard 8.5	+	+	+	+
Standard 9.0	+	+	+	+
Standard 9.5	+	+	+	+
Standard 10.0	+	+	+	+
Standard 10.5	+	+	+	+
Standard 11.0	+	+	+	+
Standard 11.5	+	+	+	+
Standard 12.0	+	+	+	+
Standard 12.5	+	+	+	+
Standard 13.0	+	+	+	+
Standard 13.5	+	+	+	+
Standard 14.0	+	+	+	+
Standard 14.5	+	+	+	+
Standard 15.0	+	+	+	+
Standard 15.5	+	+	+	+
Standard 16.0	+	+	+	+
Standard 16.5	+	+	+	+
Standard 17.0	+	+	+	+
Standard 17.5	+	+	+	+
Standard 18.0	+	+	+	+
Standard 18.5	+	+	+	+
Standard 19.0	+	+	+	+
Standard 19.5	+	+	+	+
Standard 20.0	+	+	+	+
Standard 20.5	+	+	+	+
Standard 21.0	+	+	+	+
Standard 21.5	+	+	+	+
Standard 22.0	+	+	+	+
Standard 22.5	+	+	+	+
Standard 23.0	+	+	+	+
Standard 23.5	+	+	+	+
Standard 24.0	+	+	+	+
Standard 24.5	+	+	+	+
Standard 25.0	+	+	+	+
Standard 25.5	+	+	+	+
Standard 26.0	+	+	+	+
Standard 26.5	+	+	+	+
Standard 27.0	+	+	+	+
Standard 27.5	+	+	+	+
Standard 28.0	+	+	+	+
Standard 28.5	+	+	+	+
Standard 29.0	+	+	+	+
Standard 29.5	+	+	+	+
Standard 30.0	+	+	+	+
Standard 30.5	+	+	+	+
Standard 31.0	+	+	+	+
Standard 31.5	+	+	+	+
Standard 32.0	+	+	+	+
Standard 32.5	+	+	+	+
Standard 33.0	+	+	+	+
Standard 33.5	+	+	+	+
Standard 34.0	+	+	+	+
Standard 34.5	+	+	+	+
Standard 35.0	+	+	+	+
Standard 35.5	+	+	+	+
Standard 36.0	+	+	+	+
Standard 36.5	+	+	+	+
Standard 37.0	+	+	+	+
Standard 37.5	+	+	+	+
Standard 38.0	+	+	+	+
Standard 38.5	+	+	+	+
Standard 39.0	+	+	+	+
Standard 39.5	+	+	+	+
Standard 40.0	+	+	+	+
Standard 40.5	+	+	+	+
Standard 41.0	+	+	+	+
Standard 41.5	+	+	+	+
Standard 42.0	+	+	+	+
Standard 42.5	+	+	+	+
Standard 43.0	+	+	+	+
Standard 43.5	+	+	+	+
Standard 44.0	+	+	+	+
Standard 44.5	+	+	+	+
Standard 45.0	+	+	+	+
Standard 45.5	+	+	+	+
Standard 46.0	+	+	+	+
Standard 46.5	+	+	+	+
Standard 47.0	+	+	+	+
Standard 47.5	+	+	+	+
Standard 48.0	+	+	+	+
Standard 48.5	+	+	+	+
Standard 49.0	+	+	+	+
Standard 49.5	+	+	+	+
Standard 50.0	+	+	+	+
Standard 50.5	+	+	+	+
Standard 51.0	+	+	+	+
Standard 51.5	+	+	+	+
Standard 52.0	+	+	+	+
Standard 52.5	+	+	+	+
Standard 53.0	+	+	+	+
Standard 53.5	+	+	+	+
Standard 54.0	+	+	+	+
Standard 54.5	+	+	+	+
Standard 55.0	+	+	+	+
Standard 55.5	+	+	+	+
Standard 56.0	+	+	+	+
Standard 56.5	+	+	+	+
Standard 57.0	+	+	+	+
Standard 57.5	+	+	+	+
Standard 58.0	+	+	+	+
Standard 58.5	+	+	+	+
Standard 59.0	+	+	+	+
Standard 59.5	+	+	+	+
Standard 60.0	+	+	+	+
Standard 60.5	+	+	+	+
Standard 61.0	+	+	+	+
Standard 61.5	+	+	+	+
Standard 62.0	+	+	+	+
Standard 62.5	+	+	+	+
Standard 63.0	+	+	+	+
Standard 63.5	+	+	+	+
Standard 64.0	+	+	+	+
Standard 64.5	+	+	+	+
Standard 65.0	+	+	+	+
Standard 65.5	+	+	+	+
Standard 66.0	+	+	+	+
Standard 66.5	+	+	+	+
Standard 67.0	+	+	+	+
Standard 67.5	+	+	+	+
Standard 68.0	+	+	+	+
Standard 68.5	+	+	+	+
Standard 69.0	+	+	+	+
Standard 69.5	+	+	+	+
Standard 70.0	+	+	+	+
Standard 70.5	+	+	+	+
Standard 71.0	+	+	+	+
Standard 71.5	+	+	+	+
Standard 72.0	+	+	+	+
Standard 72.5	+	+	+	+
Standard 73.0	+	+	+	+
Standard 73.5	+	+	+	+
Standard 74.0	+	+	+	+
Standard 74.5	+	+	+	+
Standard 75.0	+	+	+	+
Standard 75.5	+	+	+	+
Standard 76.0	+	+	+	+
Standard 76.5	+	+	+	+
Standard 77.0	+	+	+	+
Standard 77.5	+	+	+	+
Standard 78.0	+	+	+	+
Standard 78.5	+	+	+	+
Standard 79.0	+	+	+	+
Standard 79.5	+	+	+	+
Standard 80.0	+	+	+	+
Standard 80.5	+	+	+	+
Standard 81.0	+	+	+	+
Standard 81.5	+	+	+	+
Standard 82.0	+	+	+	+
Standard 82.5	+	+	+	+
Standard 83.0	+	+	+	+
Standard 83.5	+	+	+	+
Standard 84.0	+	+	+	+
Standard 84.5	+	+	+	+
Standard 85.0	+	+	+	+
Standard 85.5	+	+	+	+
Standard 86.0	+	+	+	+
Standard 86.5	+	+	+	+
Standard 87.0	+	+	+	+
Standard 87.5	+	+	+	+
Standard 88.0	+	+	+	+
Standard 88.5	+	+	+	+
Standard 89.0	+	+	+	+
Standard 89.5	+	+	+	+
Standard 90.0	+	+	+	+
Standard 90.5	+	+	+	+
Standard 91.0	+	+	+	+
Standard 91.5	+	+	+	+
Standard 92.0	+	+	+	+
Standard 92.5	+	+	+	+
Standard 93.0	+	+	+	+
Standard 93.5	+	+	+	+
Standard 94.0	+	+	+	+
Standard 94.5	+	+	+	+
Standard 95.0	+	+	+	+
Standard 95.5	+	+	+	+
Standard 96.0	+	+	+	+
Standard 96.5	+	+	+	+
Standard 97.0	+	+	+	+
Standard 97.5	+	+	+	+
Standard 98.0	+	+	+	+
Standard 98.5	+	+	+	+
Standard 99.0	+	+	+	+
Standard 99.5	+	+	+	+
Standard 100.0	+	+	+	+

加固型水平轨道可以耐受高达 25g 的冲击和振动。

认证



功能

R-KD 型 "加固型" 水平轨道，带有 3 孔固定槽，可耐受严苛环境

铝挤压件, 阳极氧化, 接触表面导电, 带 HP 标记

产品属性

机架宽度: 84HP

包装数量: 1

完成: 阳极氧化

长度: 431.8mm

材料: 铝

产品系列: EuropacPRO

产品类型: 水平横梁

类型: 加固型, KD

搭配: 插箱

其他产品详情

前端没有 M4 螺纹，无印刷，不带安装 19" 支架的槽口。

警告

应仅根据 nVent 的产品说明书与培训材料安装并使用 nVent 的产品。可访问 www.nvent.com 获取说明书，或者向您的 nVent 客服代表索取。错误安装、使用不当、滥用或未能完全遵守 nVent 的说明与警告，可能会造成产品故障、财产损失、严重的人身伤害及死亡和/或使得保修服务无效。

North America

All locations
+1.763.422.2661
Chat with us:
nvent.com/schroff

Europe

Straubenhardt, Germany
+49.7082.794.0
Betschdorf, France
+33.3.88.90.64.90
Warsaw, Poland
+48.22.209.98.35
Assago, Italy
+39.02.932.7141
Chat with us:
nvent.com/schroff

Asia

Shanghai, China
+86.21.2412.6943
Qingdao, China
+86.532.8771.6101
Singapore
+65.6768.5800
Shin-Yokohama, Japan
+81.45.476.0271
Chat with us:
nvent.com/schroff

Middle East & India

Dubai, United Arab
Emirates
+971.4.378.1700
Bangalore, India
+91.80.6715.2001
Istanbul, Turkey
+90.216.250.7374
Chat with us:
nvent.com/schroff



我们强大的品牌组合:

CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE