


Horizontal Rail Rear, Type AB for Rear I/O Board Guides, 84 HP

Power Utilities

物料号

34561-584



Combinations of horizontal rails and side panels

“+” = can be combined, “-” = combination not recommended

	Aluminum 1.0	Aluminum 1.5	Aluminum 2.0	Aluminum 2.5
Aluminum 1.0	-	+	+	+
Aluminum 1.5	+	+	+	+
Aluminum 2.0	+	+	+	+
Aluminum 2.5	+	+	+	+
Aluminum 3.0	-	-	-	-
Aluminum 3.5	-	-	-	-
Aluminum 4.0	-	-	-	-
Aluminum 4.5	-	-	-	-
Aluminum 5.0	-	-	-	-
Aluminum 5.5	-	-	-	-
Aluminum 6.0	-	-	-	-
Aluminum 6.5	-	-	-	-
Aluminum 7.0	-	-	-	-
Aluminum 7.5	-	-	-	-
Aluminum 8.0	-	-	-	-
Aluminum 8.5	-	-	-	-
Aluminum 9.0	-	-	-	-
Aluminum 9.5	-	-	-	-
Aluminum 10.0	-	-	-	-
Aluminum 10.5	-	-	-	-
Aluminum 11.0	-	-	-	-
Aluminum 11.5	-	-	-	-
Aluminum 12.0	-	-	-	-
Aluminum 12.5	-	-	-	-
Aluminum 13.0	-	-	-	-
Aluminum 13.5	-	-	-	-
Aluminum 14.0	-	-	-	-
Aluminum 14.5	-	-	-	-
Aluminum 15.0	-	-	-	-
Aluminum 15.5	-	-	-	-
Aluminum 16.0	-	-	-	-
Aluminum 16.5	-	-	-	-
Aluminum 17.0	-	-	-	-
Aluminum 17.5	-	-	-	-
Aluminum 18.0	-	-	-	-
Aluminum 18.5	-	-	-	-
Aluminum 19.0	-	-	-	-
Aluminum 19.5	-	-	-	-
Aluminum 20.0	-	-	-	-
Aluminum 20.5	-	-	-	-
Aluminum 21.0	-	-	-	-
Aluminum 21.5	-	-	-	-
Aluminum 22.0	-	-	-	-
Aluminum 22.5	-	-	-	-
Aluminum 23.0	-	-	-	-
Aluminum 23.5	-	-	-	-
Aluminum 24.0	-	-	-	-
Aluminum 24.5	-	-	-	-
Aluminum 25.0	-	-	-	-
Aluminum 25.5	-	-	-	-
Aluminum 26.0	-	-	-	-
Aluminum 26.5	-	-	-	-
Aluminum 27.0	-	-	-	-
Aluminum 27.5	-	-	-	-
Aluminum 28.0	-	-	-	-
Aluminum 28.5	-	-	-	-
Aluminum 29.0	-	-	-	-
Aluminum 29.5	-	-	-	-
Aluminum 30.0	-	-	-	-
Aluminum 30.5	-	-	-	-
Aluminum 31.0	-	-	-	-
Aluminum 31.5	-	-	-	-
Aluminum 32.0	-	-	-	-
Aluminum 32.5	-	-	-	-
Aluminum 33.0	-	-	-	-
Aluminum 33.5	-	-	-	-
Aluminum 34.0	-	-	-	-
Aluminum 34.5	-	-	-	-
Aluminum 35.0	-	-	-	-
Aluminum 35.5	-	-	-	-
Aluminum 36.0	-	-	-	-
Aluminum 36.5	-	-	-	-
Aluminum 37.0	-	-	-	-
Aluminum 37.5	-	-	-	-
Aluminum 38.0	-	-	-	-
Aluminum 38.5	-	-	-	-
Aluminum 39.0	-	-	-	-
Aluminum 39.5	-	-	-	-
Aluminum 40.0	-	-	-	-
Aluminum 40.5	-	-	-	-
Aluminum 41.0	-	-	-	-
Aluminum 41.5	-	-	-	-
Aluminum 42.0	-	-	-	-
Aluminum 42.5	-	-	-	-
Aluminum 43.0	-	-	-	-
Aluminum 43.5	-	-	-	-
Aluminum 44.0	-	-	-	-
Aluminum 44.5	-	-	-	-
Aluminum 45.0	-	-	-	-
Aluminum 45.5	-	-	-	-
Aluminum 46.0	-	-	-	-
Aluminum 46.5	-	-	-	-
Aluminum 47.0	-	-	-	-
Aluminum 47.5	-	-	-	-
Aluminum 48.0	-	-	-	-
Aluminum 48.5	-	-	-	-
Aluminum 49.0	-	-	-	-
Aluminum 49.5	-	-	-	-
Aluminum 50.0	-	-	-	-
Aluminum 50.5	-	-	-	-
Aluminum 51.0	-	-	-	-
Aluminum 51.5	-	-	-	-
Aluminum 52.0	-	-	-	-
Aluminum 52.5	-	-	-	-
Aluminum 53.0	-	-	-	-
Aluminum 53.5	-	-	-	-
Aluminum 54.0	-	-	-	-
Aluminum 54.5	-	-	-	-
Aluminum 55.0	-	-	-	-
Aluminum 55.5	-	-	-	-
Aluminum 56.0	-	-	-	-
Aluminum 56.5	-	-	-	-
Aluminum 57.0	-	-	-	-
Aluminum 57.5	-	-	-	-
Aluminum 58.0	-	-	-	-
Aluminum 58.5	-	-	-	-
Aluminum 59.0	-	-	-	-
Aluminum 59.5	-	-	-	-
Aluminum 60.0	-	-	-	-
Aluminum 60.5	-	-	-	-
Aluminum 61.0	-	-	-	-
Aluminum 61.5	-	-	-	-
Aluminum 62.0	-	-	-	-
Aluminum 62.5	-	-	-	-
Aluminum 63.0	-	-	-	-
Aluminum 63.5	-	-	-	-
Aluminum 64.0	-	-	-	-
Aluminum 64.5	-	-	-	-
Aluminum 65.0	-	-	-	-
Aluminum 65.5	-	-	-	-
Aluminum 66.0	-	-	-	-
Aluminum 66.5	-	-	-	-
Aluminum 67.0	-	-	-	-
Aluminum 67.5	-	-	-	-
Aluminum 68.0	-	-	-	-
Aluminum 68.5	-	-	-	-
Aluminum 69.0	-	-	-	-
Aluminum 69.5	-	-	-	-
Aluminum 70.0	-	-	-	-
Aluminum 70.5	-	-	-	-
Aluminum 71.0	-	-	-	-
Aluminum 71.5	-	-	-	-
Aluminum 72.0	-	-	-	-
Aluminum 72.5	-	-	-	-
Aluminum 73.0	-	-	-	-
Aluminum 73.5	-	-	-	-
Aluminum 74.0	-	-	-	-
Aluminum 74.5	-	-	-	-
Aluminum 75.0	-	-	-	-
Aluminum 75.5	-	-	-	-
Aluminum 76.0	-	-	-	-
Aluminum 76.5	-	-	-	-
Aluminum 77.0	-	-	-	-
Aluminum 77.5	-	-	-	-
Aluminum 78.0	-	-	-	-
Aluminum 78.5	-	-	-	-
Aluminum 79.0	-	-	-	-
Aluminum 79.5	-	-	-	-
Aluminum 80.0	-	-	-	-
Aluminum 80.5	-	-	-	-
Aluminum 81.0	-	-	-	-
Aluminum 81.5	-	-	-	-
Aluminum 82.0	-	-	-	-
Aluminum 82.5	-	-	-	-
Aluminum 83.0	-	-	-	-
Aluminum 83.5	-	-	-	-
Aluminum 84.0	-	-	-	-
Aluminum 84.5	-	-	-	-
Aluminum 85.0	-	-	-	-
Aluminum 85.5	-	-	-	-
Aluminum 86.0	-	-	-	-
Aluminum 86.5	-	-	-	-
Aluminum 87.0	-	-	-	-
Aluminum 87.5	-	-	-	-
Aluminum 88.0	-	-	-	-
Aluminum 88.5	-	-	-	-
Aluminum 89.0	-	-	-	-
Aluminum 89.5	-	-	-	-
Aluminum 90.0	-	-	-	-
Aluminum 90.5	-	-	-	-
Aluminum 91.0	-	-	-	-
Aluminum 91.5	-	-	-	-
Aluminum 92.0	-	-	-	-
Aluminum 92.5	-	-	-	-
Aluminum 93.0	-	-	-	-
Aluminum 93.5	-	-	-	-
Aluminum 94.0	-	-	-	-
Aluminum 94.5	-	-	-	-
Aluminum 95.0	-	-	-	-
Aluminum 95.5	-	-	-	-
Aluminum 96.0	-	-	-	-
Aluminum 96.5	-	-	-	-
Aluminum 97.0	-	-	-	-
Aluminum 97.5	-	-	-	-
Aluminum 98.0	-	-	-	-
Aluminum 98.5	-	-	-	-
Aluminum 99.0	-	-	-	-
Aluminum 99.5	-	-	-	-
Aluminum 100.0	-	-	-	-

Aluminum extrusion horizontal rail of the type AB (AB = support), for rear I/O card guides, with an anodized surface and conductive contact surface. Suitable for RatiopacPRO/-AIR and EuropacPRO/-rugged).

认证



功能

For CompactPCI in the area of rear I/O

For 2 × 3 U expansion, 2 horizontal rails of type AB are required

Aluminum extrusion, anodized surface, conductive contact surface, without HP markings

产品属性

产品类型: 水平横梁
产品系列: EuropacPRO; RatiopacPRO; RatiopacPRO AIR; CompacPRO; PropacPRO
类型: AB 型
机架宽度: 84 HP
长度: 431.8 mm
包装数量: 1

其他产品详情

Delivery is in standard pack multiples. Pricing is per individual item.

Please take into consideration that deliveries may be carried out in the stated SPQs (SPQ, e.g. 5 pieces, 10 pieces, 50 pieces, etc.). Differing order quantities (e.g. 2 pieces) may be changed to the next possible delivery quantity = Standard Pack Quantity.

警告

应仅根据 nVent 的产品说明书与培训材料安装并使用 nVent 的产品。可访问 www.nvent.com 获取说明书，或者向您的 nVent 客服代表索取。错误安装、使用不当、滥用或未能完全遵守 nVent 的说明与警告，可能会造成产品故障、财产损失、严重的人身伤害及死亡和/或使得保修服务无效。



我们强大的品牌组合:

CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE